

INDIA KA WIN WIN TRACTOR




VST 9045 DI+



PNEUMATIC ASSISTED
FRONT OPENING HOOD



BOW TYPE
FRONT AXLE



HEAVY DUTY
HITCH RAIL




DRY TYPE
AIR CLEANER



ROBUST
REAR AXLE



1800 KG
LIFT CAPACITY



OIL IMMERSERD
BRAKE



8+2 HEAVY DUTY
TRANSMISSION



DUAL DIAPHRAGM
CLUTCH

Crops

TECHNICAL SPECIFICATION

Key Applications



MILLETS



COTTON



MAIZE



SUGARCANE



SUNFLOWER

AGGREGATES	PARAMETERS	VST 9045 DI ⁺
ENGINE	ENGINE TYPE	TREM IIIA, NATURALLY ASPIRATED DI ENGINE
	HP CATEGORY (kW)	45 (33.55)
	NO. OF CYLINDERS	3
	RATED ENGINE SPEED	2000
	DISPLACEMENT (cc)	3120
	COOLING	WATER COOLED
	AIR CLEANER	DRY TYPE
	TORQUE Kgm (nm)	17.85 (175)
TRANSMISSION	GEAR BOX TYPE	SLIDING MESH
	NO. OF GEARS	8F + 2R
	SHIFTING PATTERN	CENTER SHIFT
	CLUTCH TYPE	DUAL DIAPHRAGM CLUTCH
	SPEED FORWARD (km/hr)	2.21 - 30.96
	SPEED REVERSE (km/hr)	2.76 - 10.89
	PEDAL TYPE	PUSH TYPE
	BRAKES	OIL IMMERSSED DISC BRAKES
	NO. OF DISCS ON EACH WHEEL SIDE	4
	STEERING	MANUAL/POWER *
	PTO	GSPTO
	PTO (MAXIMUM) SPEED	540
	POWER DRIVE	2WD
FUEL TANK	CAPACITY (L)	50
HYDRAULIC	ADDC	AUTOMATIC DRAFT AND DEPTH CONTROL (ADDC)
	LIFTING CAPACITY (kg)	1800
TYRES SIZE	FRONT	6.0 X 16
	REAR	13.6 X 28
	OVERALL LENGTH (mm)	3070
DIMENSIONS & CAPACITY	OVERALL WIDTH (mm)	1740
	OVERALL HEIGHT (mm)	1980
	WHEEL BASE (mm)	2020
	GROUND CLEARANCE (mm)	430
	TURNING RADIUS (m)	2.80
	TOTAL WEIGHT (kg)	1880

*OPTIONAL



MB PLOUGH



DUCK FOOT



ROTOVATOR



HAULAGE



DOZER



Trust of >7 lakh farmers, Legacy of >50 years



Widest working range (17 HP to 50 HP)



No.1 Power Tiller brand



1st 4WD compact Tractors



Global footprints in > 40 countries



Year on Year Growth Rate of over 20%



TILLERS TRACTORS LTD.

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91-80-67141111, e-mail: info@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions

Authorised Dealer

