

INDIA KA WIN-WIN TRACTOR



VST



VST 9054 DI



SUPER POWER PLOUGHING
WITH REVERSIBLE
MB PLOUGH



HIGH PERFORMANCE
BAILER



UNBEATABLE ROTAVATOR
APPLICATION



UNMATCHED HAULAGE
POWER

Crops

TECHNICAL SPECIFICATION

Key Applications



MILLETS



COTTON



MAIZE



SUGARCANE



SUNFLOWER

AGGREGATES	PARAMETERS	VST 9054 DI*
ENGINE	ENGINE TYPE	TREM IIIA, NATURALLY ASPIRATED DI ENGINE
	HP CATEGORY (kW)	50 (37.28)
	NO. OF CYLINDERS	3 CYLINDER
	RATED ENGINE SPEED	2200
	DISPLACEMENT (cc)	3120
	COOLING	WATER COOLED
	AIR CLEANER	DRY TYPE
	TORQUE Kgm (nm)	19.17 (188)
TRANSMISSION	GEAR BOX TYPE	SLIDING MESH
	NO. OF GEARS	8 F + 2 R
	CLUTCH TYPE	DUAL
	SPEED FORWARD (km/hr)	2.43-34.01
	SPEED REVERSE (km/hr)	3.04-11.96
	PEDAL TYPE	PUSH TYPE
	BRAKES	OIL IMMERSSED DISC BRAKE
	NO. OF DISCS ON EACH WHEEL SIDE	4
	STEERING	POWER
	PTO	STD/GSPTO *
	PTO (MAXIMUM) SPEED	540
	POWER DRIVE	2WD
FUEL TANK	CAPACITY (L)	50
HYDRAULIC	ADDC	AUTOMATIC DRAFT AND DEPTH CONTROL
	LIFTING CAPACITY (kg)	1800
TYRES SIZE	FRONT	6.5X16/7.5X16 *
	REAR	14.9 X 28 & 12 PR & 16.9 X 28 & 12 PR *
DIMENSIONS & CAPACITY	OVERALL LENGTH (mm)	3715
	OVERALL WIDTH (mm)	1820
	OVERALL HEIGHT (mm)	2270
	WHEEL BASE (mm)	2200
	GROUND CLEARANCE (mm)	460
	TURNING RADIUS (m)	2.9
	TOTAL WEIGHT (kg)	2060

*OPTIONAL



MB PLOUGH



DUCK FOOT



ROTOVATOR



HAULAGE



DOZER



Trust of >7 lakh farmers, Legacy of >50 years



Widest working range (17 HP to 50 HP)



No.1 Power Tiller brand



1st 4WD compact Tractors



Global footprints in > 40 countries



Year on Year Growth Rate of over 20%



TILLERS TRACTORS LTD.

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka, INDIA
Phone: +91-80-67141111, e-mail: info@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions

Authorised Dealer

