



4WD
22 HP



LEGACY IN NEW STYLE



**POWERFUL & FUEL
EFFICIENT ENGINE**



**HIGH
TORQUE**



**MULTI-CROP
SUITABILITY**



**ADDC -
HYDRAULICS**



**FRONT BONNET
WITH LOCK**



**HIGH SPEED
GEAR BOX**



**OIL IMMERSED
BRAKES**



NARROW TRACK



SIDE SHIFT

TECHNICAL SPECIFICATION

9 CROP EXPERT



GRAPES



POMEGRANATE



SUGARCANE



SOYABEAN



PADDY



MILLETS



VEGETABLES



MAIZE



COTTON

AGGREGATES	PARAMETERS	VST 922
ENGINE	ENGINE TYPE	TREM IIIA, NATURALLY ASPIRATED 4 STROKE ENGINE
	HP CATEGORY (kW)	22 HP (16.40 KW)
	NO. OF CYLINDERS	3
	RATED ENGINE SPEED	3000
	DISPLACEMENT (cc)	979.5
	COOLING	WATER COOLED
	AIR CLEANER	DRY TYPE
	TORQUE kgm (nm)	5.79 (56.8NM)
	PTO HP (kW)	18 (13.4 KW)
TRANSMISSION	CLUTCH TYPE	SINGLE DRY FRICTION PLATE
	GEAR BOX TYPE	SLIDING MESH
	NO. OF GEARS	6F + 2R / 8F + 2R *
	SHIFTING PATTERN	SIDE SHIFT
	SPEED FORWARD (km/hr)	1.31 - 19.30
	SPEED REVERSE (km/hr)	1.67 - 7.36
	BRAKES	OIL IMMERSED BRAKES
	STEERING	MANUAL
	PTO TYPE	DUAL SPEED PTO
	PTO (MAXIMUM) SPEED	540 & 540E
	POWER DRIVE	4 WHEEL DRIVE
FUEL TANK	CAPACITY (L)	18
HYDRAULICS	ADDC	AUTO DRAFT & DEPTH CONTROL
	THREE POINT HITCH	CATEGORY - 1
	LIFTING CAPACITY (kg)	750
TYRES SIZE	FRONT	5.00 - 12 / 6.00 - 12 *
	REAR	8.00 - 18 / 8.3 - 20 *
DIMENSIONS & CAPACITY	OVERALL LENGTH (mm)	2420
	OVERALL WIDTH (mm)	940 (STD), 1090
	OVERALL HEIGHT (mm)	1320
	WHEEL BASE (mm)	1420
	GROUND CLEARANCE (mm)	215
	TURNING RADIUS (m)	2.1
	TOTAL WEIGHT (kg)	860

* OPTIONAL



Trust of >7 lakh farmers, Legacy of >50 years



Widest working range (17 HP to 50 HP)



No.1 Power Tillage brand



1st 4WD compact Tractors



Global footprints in > 40 countries



Year on Year Growth Rate of over 20%



TILLERS TRACTORS LTD.

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91-80-67141111, e-mail: info@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions

Authorised Dealer

