



929DI EGT DUAL TRACK



VST

REGULAR TRACK

NARROW TRACK

30 HP
CATEGORY



JAPANESE TECHNOLOGY
DRIVEN DI ENGINE



HIGH TORQUE



DUAL ACTING
POWER STEERING



SUPERIOR STYLING WITH
GREAT ERGONOMICS



FRONT BONNET
WITH LOCK



MULTI-APPLICATIONS
SUITABILITY



DUAL TRACK

1800 419 0136

info@vsttractors.com

www.vsttractors.com

**9 CROP
EXPERT**



PADDY



GRAPES



MILLETS



POMEGRANATE



VEGETABLES



SUGARCANE



MAIZE



SOYABEAN



COTTON

VST 929DI EGT DUAL TRACK

TECHNICAL SPECIFICATION

AGGREGATES	PARAMETERS	VST 929 DI EGT DUAL TRACK
ENGINE	ENGINE TYPE	TREM IIIA, NATURALLY ASPIRATED 4 STROKE ENGINE
	HP (kW) CATEGORY	29 (21.62)
	NO. OF CYLINDERS	3
	RATED ENGINE SPEED	2800
	DISPLACEMENT (cc)	1331
	COOLING	WATER COOLED
	AIR CLEANER	DRY TYPE - DUAL FILTER
	TORQUE Kgm (Nm)	8.6 (84.3)
TRANSMISSION	PTO HP (kW)	24 (17.9)
	CLUTCH TYPE	SINGLE DRY FRICTION PLATE
	GEAR BOX TYPE	CONSTANT MESH
	NO. OF GEARS	8 FORWARD + 2 REVERSE
	SHIFTING PATTERN	SIDE SHIFT
	SPEED FORWARD (km/hr)	1.56 - 20.26
	SPEED REVERSE (km/hr)	1.39 - 5.05
	BRAKES	OIL IMMERSED BRAKES
	STEERING	POWER
	PTO	DUAL PTO
	PTO (MAXIMUM) SPEED	540, 540E
FUEL TANK	POWER DRIVE	4 WHEEL DRIVE
	CAPACITY (L)	24
HYDRAULICS	ADDC	AUTO DRAFT & DEPTH CONTROL
	THREE POINT HITCH	CATEGORY - 1
	LIFTING CAPACITY (kg)	750
TYRES SIZE	FRONT	6 X 12
	REAR	8.30 X 20
DIMENSIONS & CAPACITY	OVERALL LENGTH (mm)	2530
	OVERALL WIDTH (mm)	960 - 1095
	OVERALL HEIGHT (mm)	1323
	WHEEL BASE (mm)	1520
	GROUND CLEARANCE (mm)	325
	TURNING RADIUS (m)	2.1
	TOTAL WEIGHT (kg)	860 WITHOUT BALLAST



Trust of >7 lakh farmers,
Legacy of >50 years



No. 1 Power Tiller brand



Global footprints
in > 40 countries



Widest working range
(17 HP to 50 HP)



1st 4WD
compact Tractors



Year on Year Growth
Rate of over 20%

 **TILLERS
TRACTORS LTD.**

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91-80-67141111, e-mail: info@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice.
Performance of the machine may vary with user/field/working conditions

Authorised Dealer



1800 419 0136

 vsttillers

 vst-tillers

 VST Tillers Tractors Limited