

THE NEW CLASSIC SERIES



VST



MT-180D



POWERFUL & FUEL
EFFICIENT ENGINE



HIGH
TORQUE



3D
COOLING



750 KG
HYDRAULIC LIFT

Key Features

TECHNICAL SPECIFICATION

Key Applications



NARROWEST WIDTH



OIL IMMersed BRAKES



POWER STEERING *



BIGGER TYRE 8.3X20



ADJUSTABLE SUSPENDED SEAT

AGGREGATES

PARAMETERS

VST MT-180D

ENGINE	ENGINE TYPE	TREM IIIA, NATURALLY ASPIRATED 4 STROKE ENGINE
	HP CATEGORY (kW)	18.5 (13.79)
	NO. OF CYLINDERS	3
	RATED ENGINE SPEED	2700
	DISPLACEMENT (cc)	979.5
	COOLING	WATER COOLED
	AIR CLEANER	DRY TYPE
	TORQUE kgm (nm)	5.5 (54)
TRANSMISSION	PTO HP (kW)	15.8 (11.8)
	CLUTCH TYPE	SINGLE DRY FRICTION PLATE
	GEAR BOX TYPE	SLIDING MESH
	NO. OF GEARS	6F + 2R / 8F + 2R
	SHIFTING PATTERN	CENTER SHIFT
	SPEED FORWARD (km/hr)	1.89 - 19.11 / 2.35 - 23.15
	SPEED REVERSE (km/hr)	2.41 - 7.30 / 2.09- 7.63
	BRAKES	OIL IMMersed DISC BRAKES
	STEERING	MANUAL/POWER *
	PTO TYPE	SINGLE SPEED PTO
FUEL TANK	PTO (MAXIMUM) SPEED	540 & 540E
	POWER DRIVE	4 WHEEL DRIVE
HYDRAULICS	CAPACITY (L)	18
	ADDC	AUTO DRAFT & DEPTH CONTROL
	THREE POINT HITCH	CATEGORY - 1
TYRES SIZE	LIFTING CAPACITY (kg)	750
	FRONT	5 X 12/6 X 12
	REAR	8 X 18/8.3 X 20
DIMENSIONS & CAPACITY	OVERALL LENGTH (mm)	2705
	OVERALL WIDTH (mm)	920
	OVERALL HEIGHT (mm)	1200
	WHEEL BASE (mm)	1420
	GROUND CLEARANCE (mm)	215
	TURNING RADIUS (m)	2.3
	TOTAL WEIGHT (kg)	840

*OPTIONAL



CULTIVATOR



SEED DRILL



RIDGER



ROTARY TILLER



SPRAYER



Trust of >7 lakh farmers, Legacy of >50 years



Widest working range (17 HP to 50 HP)



No.1 Power Tiller brand



1st 4WD compact Tractors



Global footprints in > 40 countries



Year on Year Growth Rate of over 20%

TILLERS
TRACTORS LTD.

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91-80-67141111, e-mail: info@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions

Authorised Dealer



scan for more information