



932 DI & 939 DI

- 2WD & 4WD



VST

Presenting the

OWNER'S TRACTOR



THE PLEASURE OF COMFORT:

- Smooth vibration-free drive
- First platform tractor
- Easy gear shifting with fully synchromesh transmission
- Side shift for maximum comfort
- Adjustable suspended seat



EASE OF WORK:

- Independent PTO, Reverse PTO & Mid PTO
- Finger touch control with double actuating power steering
- Versatile application compatibility for the first time in compact tractors



THE LUXURY OF A CAR:

- Lowest noise tractor
- New-gen instrument cluster
- The comfort of a side shift
- Sleek styling
- Shift gears like your car



932 DI 2WD/4WD & 939 DI 2WD/4WD

Crops

TECHNICAL SPECIFICATION

Key Applications



POMEGRANATE



PADDY



ARECANUT



MILLETS



POTATO

AGGREGATES	PARAMETERS	VST 932 DI 2WD/4WD	VST 939 DI 2WD/4WD
ENGINE	ENGINE TYPE	TREM IIIA, NATURALLY ASPIRATED DI ENGINE	
	HP CATEGORY (kW)	32 (23.8)	39 (29.08)
	NO. OF CYLINDERS	3	
	RATED ENGINE SPEED	2500	3000
	DISPLACEMENT (cc)	1642	
	COOLING	WATER COOLED	
	AIR CLEANER	DRY TYPE	
	TORQUE kgm (nm)	109.4 (11.15)	107.2 (10.93)
	PTO HP (kW)	24 (18.65)	28.85 (21.51)
	GEAR BOX TYPE	FULLY SYNCHROMESH	
TRANSMISSION	NO. OF GEARS	9 FORWARD + 3 REVERSE	
	SHIFTING PATTERN	SIDE SHIFT	
	SPEED FORWARD (km/hr)	2.08-22.3/2.08-25.65	2.28-28.05
	SPEED REVERSE (km/hr)	2.21-13.86	2.42-15.18
	CLUTCH TYPE	DOUBLE CLUTCH	
	IPTO	540@2340, 1004@2500	
	RPTO (MAXIMUM) SPEED	540@1937	
	MID PTO	MID PTO	
	BRAKES	OIL IMMersed BRAKES	
	STEERING	POWER	
FUEL TANK	POWER DRIVE	2WD/4WD	
	CAPACITY (L)	25	
HYDRAULICS	ADDC	AUTO DRAFT & DEPTH CONTROL	
	THREE POINT HITCH	CATEGORY I & II	
	LIFTING CAPACITY (kg)	1250	
	FRONT - 2WD	5 X 15	
TYRES SIZE	FRONT - 4WD	6 X 12, 7 X 14	
	REAR	9.5 X 20, 11.2 X 24	
DIMENSIONS & CAPACITY	OVERALL LENGTH (mm)	2510	2540
	OVERALL WIDTH (mm)	FRONT: 1070, 1190	FRONT: 1190
		REAR: 1130 (STD), 1470	REAR: 1245/1130, 1470
	OVERALL HEIGHT (mm)	1390	1400
	WHEEL BASE (mm)	1520	
	GROUND CLEARANCE (mm)	325	330
	TURNING RADIUS (m)	2.5	
	TOTAL WEIGHT (kg)	1240 (UNBALLASTED)	1260 (UNBALLASTED)



MB PLOUGH



DUCK FOOT/
BALARAM



CULTIVATOR



ROTAVATOR



HAULAGE

AGGREGATES	VST 932 DI	COMPETITION 1	COMPETITION 2	COMPETITION 3	RS.58000 EXTRA VALUE THAN COMPETITION
HP Category	32	30	24	28	Rs.20000 Extra value HP
No. of Cylinder	3	2	2	2	NVH free tractor - better driving experience, better health
Gearbox Type	9+3 Synchromesh	8+2 Sliding Mesh	6+2 Sliding Mesh	8+2 Sliding Mesh	Rs.15000 Extra value feature - fully synchro, 9+3, HLM
PTO Type	IPTO	Normal PTO	Normal PTO	Normal PTO	Rs.8000 Extra value feature with IPTO
	RPTO	Not available	Not available	Not available	Rs.5000 Extra value feature with RPTO
PTO Power (HP)	24	20.3	19.98	25.8	Less power loss - more PTO power, high performance
Engine Oil Consumption (L)	4	5	6	6	Rs.3000 Extra saving on engine oil
Transmission Oil Consumption (L)	28	27	30.5	46	Rs.7000 Extra saving on transmission oil

IPTO - Independent PTO, RPTO - Reverse PTO, NVH - Noise, Vibration, Heat, HP - Horsepower



Trust of >7 lakh farmers,
Legacy of >50 years



Widest working range
(17 HP to 50 HP)



No.1 Power Tiller
brand



1st 4WD
compact Tractors



Global footprints
in > 40 countries



Year on Year Growth
Rate of over 20%



**TILLERS
TRACTORS LTD.**

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91-80-67141111, e-mail: info@vsttractors.com,
CIN: L34101KA1967PLC001706. www.vsttractors.com

Authorised Dealer



scan for more information

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions

1800 419 0136

Grow with us