



929DI EGT DUAL TRACK

2WD / 4WD

**29 HP
CATEGORY**



JAPANESE TECHNOLOGY
DRIVEN DI ENGINE



HIGH
TORQUE



DUAL ACTING
POWER STEERING



SUPERIOR STYLING WITH
GREAT ERGONOMICS



FRONT BONNET
WITH LOCK



MULTI-APPLICATIONS
SUITABILITY



DUAL
TRACK



1800 419 0136



info@vsttractors.com



www.vsttractors.com



TECHNICAL SPECIFICATION

AGGREGATES	PARAMETERS	VST 929 DI EGT 4WD	VST 929 DI EGT 2WD
ENGINE	Type	Trem IIIA, Naturally Aspirated 4 Stroke Engine	Trem IIIA, Naturally Aspirated 4 Stroke Engine
	HP (kW) Category	29 (21.62)	29 (21.62)
	No. of Cylinders	3	3
	Rated RPM	2800	2800
	Displacement (cc)	1331	1331
	Cooling	Water Cooled	Water Cooled
	Air Cleaner	Dry Type	Dry Type
	Torque Kg-m (Nm)	8.6 (84.3)	8.6 (84.3)
TRANSMISSION	PTO HP (kW)	22 (16.40)	25 (18.65)
	Clutch	Single Dry Friction Plate	Single Dry Friction Plate
	Gear Box Type	Constant Mesh	Constant Mesh
	No. of Gears	8 Forward + 2 Reverse	8 Forward + 2 Reverse
	Shifting	Side Shift	Side Shift
	Speed Forward (km/hr)	1.57 - 19.12	1.84 - 22.54
BRAKES	Speed Reverse (km/hr)	1.40 - 5.09	1.64 - 6.00
	Type	Oil Immersed Brakes	Oil Immersed Brakes
STEERING	Type	Power Steering	Power Steering
PTO	Type	Dual PTO	Dual Speed PTO
	RPM	540, 540E	540, 540E
FUEL TANK	Capacity (ltrs)	25	25
HYDRAULICS	Type	Automatic Depth & Draft Control (ADDC)	Automatic Depth & Draft Control (ADDC)
	Three Point Hitch	Category - 1	Category - 1 & 2
	Lifting Capacity (kg)	1050	1050
TYRES	Wheel Drive	4 Wheel Drive	2 Wheel Drive
	Front - inches (mm)	6 - 12 (152.4-304.8), 7 - 14 (177.8-355.6)	5 - 15 (127-381)
	Rear - inches (mm)	8.30 - 20 (210.8-508), 9.5 - 20 (248.9-508)	9.5 - 24 (241.3-609.6)
	Overall Length (mm)	2530	2620
DIMENSIONS	Overall Width (mm)	960 - 1080	1117
	Overall Height (mm)	1330	1409
	Wheel Base (mm)	1520	1530
	Ground Clearance (mm)	330	340
	TCR with Brakes (m)	2.1	2.4
	Total Weight (Kg)	860 without ballast	1015



Trust of >5 Lakh Farmers,
Legacy of >55 Years



Widest Product Range
(17 HP to 50 HP)



No.1 Power Tiller
Brand



1st 4 Wheel Drive (WD)b
Compact Tractors



Global Footprints
in > 40 Countries



Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91 - 80 - 67141111, e-mail: info@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.

1800 419 0136

f /vsttillers

in /company/vst-tillers

http://bit.ly/VSTVideos

