



VST

THE NEW CLASSIC SERIES



VST 171 DI



**POWERFUL & FUEL
EFFICIENT ENGINE**



**HIGH
TORQUE**



**3D
COOLING**



**750 KG
HYDRAULIC LIFT**

Key Features

TECHNICAL SPECIFICATION

Key Applications



NARROWEST WIDTH



OIL IMMERSSED BRAKES



POWER STEERING *



HEAVY-DUTY REAR AXLE



DRY TYPE AIR CLEANER

AGGREGATES	PARAMETERS	VST 171 DI
ENGINE	ENGINE TYPE	TREM IIIA, NATURALLY ASPIRATED 4 STROKE ENGINE
	HP CATEGORY (kW)	17 (12.67)
	NO. OF CYLINDERS	1
	RATED ENGINE SPEED	2400
	DISPLACEMENT (cc)	857
	COOLING	WATER COOLED
	AIR CLEANER	DRY TYPE
	TORQUE kgm (nm)	5.5 (54)
	PTO HP (kW)	13.4 (10)
TRANSMISSION	CLUTCH TYPE	SINGLE DRY FRICTION PLATE
	GEAR BOX TYPE	SLIDING MESH
	NO. OF GEARS	6F + 2R
	SHIFTING PATTERN	CENTER SHIFT
	SPEED FORWARD (km/hr)	1.97 - 24.31
	SPEED REVERSE (km/hr)	2.52 - 11.07
	BRAKES	OIL IMMERSSED DISC BRAKES
	STEERING	MANUAL/POWER *
	PTO TYPE	SINGLE SPEED PTO
	PTO (MAXIMUM) SPEED	540@1900
POWER DRIVE	2 WHEEL DRIVE	
FUEL TANK	CAPACITY (L)	18
HYDRAULICS	ADDC	AUTO DRAFT & DEPTH CONTROL
	THREE POINT HITCH	CATEGORY - 1
	LIFTING CAPACITY (kg)	750
TYRES SIZE	FRONT	4.5 X 12/5.25 X 14
	REAR	8 X 18
DIMENSIONS & CAPACITY	OVERALL LENGTH (mm)	2315
	OVERALL WIDTH (mm)	910
	OVERALL HEIGHT (mm)	1795
	WHEEL BASE (mm)	1456
	GROUND CLEARANCE (mm)	280
	TURNING RADIUS (m)	2.3
	TOTAL WEIGHT (kg)	798

* OPTIONAL



CULTIVATOR



SEED DRILL



RIDGER



BLADE CULTIVATOR



HAULAGE



Trust of >7 lakh farmers, Legacy of >50 years



Widest working range (17 HP to 50 HP)



No.1 Power Tiller brand



1st 4WD compact Tractors



Global footprints in > 40 countries



Year on Year Growth Rate of over 20%



Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
 Phone: +91-80-67141111, e-mail: info@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Authorised Dealer



scan for more information

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions