

**THE NEW
CLASSIC SERIES**



VST

Rugged

Radiant

Reliable



AJAI POWER PLUS



**POWERFUL & FUEL
EFFICIENT ENGINE**



**HIGH
TORQUE**



**3D
COOLING**



**750 KG
HYDRAULIC LIFT**

 1800 419 0136

 info@vstractors.com

 www.vstractors.com

Key Features

TECHNICAL SPECIFICATION

Key Applications



**NARROWEST
WIDTH**



**OIL IMMERSSED
BRAKES**



**POWER
STEERING**



**BIGGER TYRE
8.3X20**



**ADJUSTABLE SEAT
WITH SUSPENSION**

AGGREGATES	PARAMETERS	VST MT 225 AJAI POWER PLUS
ENGINE	ENGINE TYPE	TREM IIIA, NATURALLY ASPIRATED 4 STROKE ENGINE
	HP CATEGORY (kW)	22 (16.40)
	NO. OF CYLINDERS	3
	RATED ENGINE SPEED	3000
	DISPLACEMENT (cc)	979.5
	COOLING	WATER COOLED
	AIR CLEANER	DRY TYPE
	TORQUE kgm (nm)	5.7 (56)
	PTO HP (kW)	14.2 (19)
TRANSMISSION	CLUTCH TYPE	SINGLE DRY FRICTION PLATE
	GEAR BOX TYPE	CONSTANT MESH
	NO. OF GEARS	8F + 2R
	SHIFTING PATTERN	SIDE SHIFT
	SPEED FORWARD (km/hr)	2.61 - 25.80
	SPEED REVERSE (km/hr)	2.25 - 8.21
	BRAKES	OIL IMMERSSED DISC BRAKES
	STEERING	MANUAL/POWER *
	PTO TYPE	DUAL SPEED PTO
	PTO (MAXIMUM) SPEED	540 & 540E
POWER DRIVE	4 WHEEL DRIVE	
FUEL TANK	CAPACITY (L)	18
HYDRAULICS	ADDC	AUTO DRAFT & DEPTH CONTROL
	THREE POINT HITCH	CATEGORY - 1
	LIFTING CAPACITY (kg)	750
TYRES SIZE	FRONT	*5 X 12/6 X 12
	REAR	*8 X 18/8.3 X 20
DIMENSIONS & CAPACITY	OVERALL LENGTH (mm)	2402
	OVERALL WIDTH (mm)	920
	OVERALL HEIGHT (mm)	1320
	WHEEL BASE (mm)	1420
	GROUND CLEARANCE (mm)	215
	TURNING RADIUS (m)	2.3
TOTAL WEIGHT (kg)	860	

*OPTIONAL



CULTIVATOR



SEED DRILL



RIDGER



ROTARY TILLER



SPRAYER



Trust of >7 lakh farmers, Legacy of >50 years



Widest working range (17 HP to 50 HP)



No.1 Power Tiller brand



1st 4WD compact Tractors



Global footprints in > 40 countries



Year on Year Growth Rate of over 20%



**VST TILLERS
TRACTORS LTD.**

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91-80-67141111, e-mail: info@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions

Authorised Dealer



scan for more information