

THE NEW
CLASSIC SERIES



VST

Rugged Radiant Reliable



VST MT 270



POWERFUL & FUEL
EFFICIENT ENGINE



HIGH
TORQUE



3D
COOLING



750 KG
HYDRAULIC LIFT

1800 419 0136

info@vstractors.com

www.vstractors.com

Key Features

TECHNICAL SPECIFICATION

Key Applications



**NARROWEST
WIDTH**



**OIL IMMERSSED
BRAKES**



**POWER
STEERING**



**BIGGER TYRE
8.3X20**



**ADJUSTABLE SEAT
WITH SUSPENSION**

AGGREGATES	PARAMETERS	VST MT 270 AGRIMASTER
ENGINE	ENGINE TYPE	TREM IIIA, NATURALLY ASPIRATED 4 STROKE ENGINE
	HP CATEGORY (kW)	27 (20.13)
	NO. OF CYLINDERS	4
	RATED ENGINE SPEED	2800
	DISPLACEMENT (cc)	1306
	COOLING	WATER COOLED
	AIR CLEANER	DRY TYPE
	TORQUE kgm (nm)	7.34 (72)
TRANSMISSION	PTO HP (kW)	17.9 (24)
	CLUTCH TYPE	SINGLE DRY FRICTION PLATE
	GEAR BOX TYPE	CONSTANT MESH
	NO. OF GEARS	8F + 2R
	SHIFTING PATTERN	SIDE SHIFT
	SPEED FORWARD (km/hr)	1.96 - 19.81 / 2.44 - 24.01
	SPEED REVERSE (km/hr)	2.49 - 7.57 / 2.17 - 7.92
	BRAKES	OIL IMMERSSED DISC BRAKES
	STEERING	POWER
	PTO TYPE	DUAL SPEED PTO
FUEL TANK	PTO (MAXIMUM) SPEED	540 & 540E
	POWER DRIVE	4 WHEEL DRIVE
HYDRAULICS	CAPACITY (L)	18
	ADDC	AUTOMATIC DRAFT AND DEPTH CONTROL
	THREE POINT HITCH	CATEGORY - 1
TYRES SIZE	LIFTING CAPACITY (kg)	750
	FRONT	6 X 12
	REAR	8.3 X 20
DIMENSIONS & CAPACITY	OVERALL LENGTH (mm)	2845
	OVERALL WIDTH (mm)	920
	OVERALL HEIGHT (mm)	1320
	WHEEL BASE (mm)	1420
	GROUND CLEARANCE (mm)	255
	TURNING RADIUS (m)	2.3
TOTAL WEIGHT (kg)	980	



CULTIVATOR



SEED DRILL



RIDGER



ROTARY TILLER



SPRAYER



Trust of >7 lakh
farmers, Legacy of
>50 years



Widest working range
(17 HP to 50 HP)



No.1 Power Tiller
brand



1st 4WD
compact Tractors



Global footprints
in > 40 countries



Year on Year
Growth Rate of
over 20%



**VST TILLERS
TRACTORS LTD.**

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91-80-67141111, e-mail: info@vsttractors.com,
CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions

Authorised Dealer



scan for more information