



927

LEGACY IN NEW STYLE



4WD
24 HP



Futuristic Styling



Power-puddling Enabled



Designed for All Orchard Applications



Oil Immersed Brakes



Precision Hydraulic Lifting up to 750 Kg



Sugarcane Applications



Power Steering

1800 419 0136

info@vstractors.com

www.vstractors.com



TECHNICAL SPECIFICATION

AGGREGATES	PARAMETERS	Sugarcane	Spraying	Puddling
ENGINE	Type	Trem IIIA, Naturally Aspirated DI Engine		
	HP (kW)	24 (17.89)		
	No. of Cylinders	4		
	Rated RPM	2700		
	Displacement (cc)	1306		
	Cooling	Water Cooled		
	Air Cleaner	Dry Type		
	Torque Kg-m (Nm)	7.14 (70)		
	PTO HP (kW)	19.1(14.24)		
TRANSMISSION	Clutch	Single Dry Friction Plate		
	Gear Box Type	Sliding Mesh		
	No. of Gears	6 Forward + 2 Reverse		
	Shifting	Side Shift		
	Speed Forward (km/hr)	1.51 - 17.09	1.68 - 24.68	1.68 - 19.01
Speed Reverse (km/hr)	1.51 - 6.66	1.85 - 8.06	1.85 - 8.06	
BRAKES	Type	Oil Immersed Brakes		
STEERING	Type	Power Assisted Steering		
PTO	Type	Two Speed PTO		
	PTO (rpm)	646 & 953	549 & 810	646 & 953
FUEL TANK	Capacity (ltrs)	18		
HYDRAULICS	Type	Automatic Draft & Depth Control (ADDC)		
	Three Point Hitch	Category - 1		
	Lifting Capacity (kg)	750		
TYRES	Wheel Drive	4 Wheel Drive		
	Front	5 x 12	6 x 12	6 x 12
	Rear	8 x 18	8.3 x 20	8.3 x 20
DIMENSIONS	Overall Length (mm)	2435	2450	2435
	Overall Width (mm)	940, 1090	1000, 1080	1000, 1080
	Overall Height (mm)	1350		
	Wheel Base (mm)	1420		
	Ground Clearance (mm)	250		
	TCR with Brakes (m)	2.1		
	Total Weight (Kg)	784		



Trust of >5 Lakh Farmers,
Legacy of >50 Years



Widest Working Range
(17 HP to 50 HP)



No.1 Power Tiller Brand
for Last 50 Years



Pioneer in 4WD
Compact Tractors



Global Footprints
in > 40 Countries



Year on Year Growth
Rate of over 20%

Please contact your nearest dealership for latest updates

Authorized Dealer



TILLERS TRACTORS LTD.

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91 - 80 - 67141111, e-mail: info@vsttractors.com,
CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.

