POWER TILLER A TRUST BUILT OVER DECADES













Light Weight



Easy Turning

MADE IN INDIA ·····

APPLICATIONS: Dry Land & Wet Land Operation, Inter-cultivation, Earthing-up, Land Preparation etc.

SUITABLE FOR: Vegetable Crops, Horticulture Crops & Plantation Crops







TECHNICAL SPECIFICATIONS

ENGINE				
MODEL	VST 130 DI			
Туре	Horizontal 4 stroke single cylinder water cooled diesel engine OHV			
Combustion Chamber	Direct Injection (DI)			
Max. Torque	4.2 kg-m/1600 rpm			
Max. HP as per IS 13539 1996	13.0 HP@2400 rpm			
SFC (Specific Fuel Cons)	190g/hp/hr			
Governor System	Mechanical, centrifugal type			
Cooling System	Condenser type thermo siphon cooling system			
Starting System	Hand cranking			
Lighting System	12 Volts/35 Watts			
Std. Pulley (DIA)	100mm/optional 120mm			
Dry Weight	125 kgs			
LUBRICATING SYSTEM				
Oil Sump Capacity	2.8 ltrs			
Type of Lubricating System	Force feed type Trochoid pump			
Air Cleaner	Multistage, oil bath type with cyclonic per-cleaner			
PERFORMANCE				
Tilling Width	600 mm (maximum)			
No. of Tynes	18			
Tilling Depth	150 mm (maximum)			
Plough Depth	220 mm (maximum)			

Туре		Side drive rotary transmission		
Forward		6 speeds		
Reverse		2 speeds		
Rotary		2 speeds		
Clutch		Multiple plate dry disc type		
Brake		Hand operated internal expanding metallic shoe type		
Weight		280 kgs		
FUEL SYSTEM				
Fuel		High speed diesel		
Fuel Tank Capacity		11 ltrs		
Nozzle		Multi-hole (5)		
	SPE	ED (Kmp	h)	
GEAR	STANDARD P	ULLEY	OPTIONAL PULLEY	
GEAR		DRWARD	OPTIONAL PULLEY	
GEAR 1L			OPTIONAL PULLEY	
	F			
1L	F(1.78	
1L 2	1.48 2.18		1.78 2.62	
1L 2 3	1.48 2.18 3.43		1.78 2.62 4.11	
1L 2 3 4H	1.48 2.18 3.43 5.26		1.78 2.62 4.11 6.31	
1L 2 3 4H 5	1.48 2.18 3.43 5.26 7.72 12.18		1.78 2.62 4.11 6.31 9.26	
1L 2 3 4H 5	1.48 2.18 3.43 5.26 7.72 12.18	DRWARD	1.78 2.62 4.11 6.31 9.26	
1L 2 3 4H 5 6	1.48 2.18 3.43 5.26 7.72 12.18	DRWARD	1.78 2.62 4.11 6.31 9.26 14.61	
1L 2 3 4H 5 6	1.48 2.18 3.43 5.26 7.72 12.18	DRWARD	1.78 2.62 4.11 6.31 9.26 14.61	
1L 2 3 4H 5 6	1.48 2.18 3.43 5.26 7.72 12.18 R 1.28 4.56	DRWARD REVERSE	1.78 2.62 4.11 6.31 9.26 14.61 1.53 5.47	

TILLER TRANSMISSION



Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA Phone: +91 - 80 - 67141111, e-mail: tollfree@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Authorised Dealer

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.

