

Asli tractor ki pehchan.



VST 171DI



Asli
high-torque



Asli
comfort



Asli
bachat

SPECIFICATIONS

Engine Model

Engine	Single Cylinder DI Engine
Displacement (swept volume) cc	857
Output (HP) @ Rated (rpm)	17 @2400
Max. Torque (kg-m) @ (rpm)	5.5 @ 1600
Cooling system	Water cooled

Transmission

Constant Mesh	6F + 2R
Gear Lever	Center Shift
Speed Range (km / hr)	Forward: 1.94 - 24.01 Reverse: 1.9 - 11.40
STD PTO (rpm)	540
PTO (HP)	13.04
Differential	Bevel Gear
Brake	Dry Disc Brake
Clutch	Single
Steering	Mechanical

Fuel System

Fuel	High speed diesel
Fuel Tank Capacity (ltrs)	18
Air Cleaner	Wet type

Hydraulic System

Smart Hydraulic System	Auto Draft & Depth Control (ADDC)
Lifting Capacity (kg)	750
Haulage (tonnes)	3
Three Point Linkage	Cat - 1 N

Overall Dimensions

Overall Dimensions (LxBxH) (mm)	2315 x 1091 x 1795
Ground Clearance (mm)	280
Turning Radius (m)	2.3
Weight (kg)	798
Wheel Base (mm)	1456
Wheel Track - Tyre Outer to Outer (mm)	
	Front 870
	Rear 885
Tyre	Front 5.25 x 14
	Rear 8 x 18



Trust of >5 lakh farmers,
Legacy of >50 years



Widest working range
(3 HP to 50 HP)



No.1 Power Tiller brand
for last 50 years



Pioneer in light weight
4WD compact Tractors



Global footprints in
> 40 countries



**TILLERS
TRACTORS LTD.**

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91 - 80 - 67141111, e-mail: info@vsttractors.com,
CIN: L34101KA1967PLC001706. www.vsttractors.com

Authorised Dealer

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice.
Performance of the machine may vary with user/field/working conditions.

1800 419 0136

/vsttillers

/company/vst-tillers

<http://bit.ly/VSTVideos>

