



Authorised dealer:



CIN-L34101KA1967PLC001706  
Plot No.1 Dyavasandra Indl. Layout, Whitefield Road,  
Mahadevapura Post, Bengaluru-560048, India.



info@vsttractors.com

www.vsttractors.com

/vst-tillers

http://bit.ly/VSTVideos

company/vst-tillers

Grow with us

CUSTOMER HELPLINE: 1800 4190 136



DOMESTIC & AGRICULTURE PUMPS



PUMPS CATALOGUE & SELECTION GUIDE

Grow with us

CUSTOMER HELPLINE: 1800 4190 136



# OPENWELL PUMPS



## FEATURES

Made with CNC technology

High operating Efficiency

Corrosion & abrasive resistance parts made of SS

Dynamic balancing of rotating components

Reliable thrust bearing and sleeve



APARTMENTS



GARDENING



VILLA

Grow with us



## PRODUCT SPECIFICATIONS

Pump Sizes (MM): 25X25

Head (M): Up to 30

Discharge (LPM): Up to 180

Power Range (HP): Up to 1.0

RPM: 2800

Voltage Range (V): 160 to 240



## OPENWELL PUMPS

### MATERIAL OF CONSTRUCTION (MOC)

Pump Casing	Cast Iron
Impeller	Noryl
Shaft	SS410
Bush	Carbon
Insulation	Class B / Class F
Motor Body	SS 202

### PERFORMANCE TABLE

SR. No.	MODEL	H.P./kW	VOLTAGE (V)	SUPPLY TYPE	SUCTION X DELIVERY (mm)	DISCHARGE IN LPH	HEAD IN METERS									
							9	11	12.5	14.5	14	17.7	19.5	20	-	-
	0.5 OW	0.5/0.37	160-240	1PH	25X25	150	132	126	108	90	72	60	30	-	-	
	1 OW	1.0/0.75	160-240	1PH	25X25	180	162	132	108	90	72	60	30	-	-	
	1 OW S	1.0/0.75	160-240	1PH	25X25	160	155	150	138	114	84	47	18	-	-	

NOTE: Technical details are approximate and may change due to site conditions or due to continuous improvement

CUSTOMER HELPLINE: 1800 4190 136