



Authorised dealer:



CIN-L34101KA1967PLC001706
Plot No.1 Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, India.



info@vsttractors.com

www.vsttractors.com

/vst-tillers

http://bit.ly/VSTVideos

company/vst-tillers

Grow with us

CUSTOMER HELPLINE: 1800 4190 136



DOMESTIC & AGRICULTURE PUMPS



PUMPS CATALOGUE & SELECTION GUIDE

Grow with us

CUSTOMER HELPLINE: 1800 4190 136

SELF PRIMING PUMPS



FEATURES

Automatic coil winding and CNC technology

Thermal Overload Protector (TOP)

Double shielded pre-lubricated ball bearings

Water resistant terminal box for safety

Suction lift up to 7mtr



APARTMENTS



GARDENING



VILLA

Grow with us



PRODUCT SPECIFICATIONS

Pump Sizes (MM): 25X25

Head (M): Up to 56

Discharge (LPH): Up to 3900

Power Range (HP): Up to 1.0

RPM: 2800

Voltage Range (V): 180 to 240 & 180 to 280 (HV)

MATERIAL OF CONSTRUCTION (MOC)

Pump Casing	Cast Iron
Impeller	Forged Brass
Shaft	EN8 / SS410
Mechanical Seal	Carbon / Ceramic
Insulation	Class B / Class F
Motor Body	Aluminum / PDC/ CI



SELF PRIMING PUMPS

PERFORMANCE TABLE

SR. No.	MODEL	H.P./KW	VOLTAGE (V)	SUPPLY TYPE	SUCTION X DELIVERY (mm)	DISCHARGE IN LPH	HEAD IN METERS																					
							6	9	12	15	18	21	24	26	28	32	34	36	40	50	56							
	0.5 SP	0.5 / 0.37	220	1PH	25x25	1900	1750	1400	1150	900	750	550	400	250														
	0.5 SP+	0.5 / 0.37	220	1PH	25x25	2000	1800	1400	1200	1000	800	600	400	300														
	1.0 SP	1.0/0.75	220	1PH	25x25	2900	2800	2450	2200	1800	1500	1200	1000	900	700	300												
	1.0 SP+	1.0/0.75	220	1PH	25x25	3250	3090	2750	2400	2150	1900	1600	1400	1250	820	500	300											
	1.0 SP++	1.0/0.75	220	1PH	25x25	2800	2550	2450	2350	2100	1800	1600	1500	1350	1050	650	550											
	1.0 SPP	1.0/0.75	220	1PH	25x25	3924	3890	3810	3744	3515	3210	3100	2980	2720	2600	2440	2305	2124	1260	648								

NOTE: Technical details are approximate and may change due to site conditions or due to continuous improvement

CUSTOMER HELPLINE: 1800 4190 136