



Authorised dealer:



CIN-L34101KA1967PLC001706  
Plot No.1 Dyavasandra Indl. Layout, Whitefield Road,  
Mahadevapura Post, Bengaluru-560048, India.



info@vsttractors.com

www.vsttractors.com

/vst-tillers

http://bit.ly/VSTVideos

company/vst-tillers

Grow with us

CUSTOMER HELPLINE: 1800 4190 136



## DOMESTIC & AGRICULTURE PUMPS



PUMPS CATALOGUE & SELECTION GUIDE

Grow with us

CUSTOMER HELPLINE: 1800 4190 136

# SHALLOW WELL PUMPS



## FEATURES

Automatic coil winding and CNC technology

Thermal Overload Protector (TOP)

Double shielded pre-lubricated ball bearings

Water resistant terminal box for safety

Suction lift up to 8mtr



APARTMENTS



GARDENING



VILLA

Grow with us



## PRODUCT SPECIFICATIONS

Pump Sizes (MM): 25X25

Head (M): Up to 40

Discharge (LPH): Up to 3900

Power Range (HP): Up to 1.0

RPM: 2800

Voltage Range (V): 180 to 240 & 180 to 280 (HV)

## MATERIAL OF CONSTRUCTION (MOC)

Pump Casing	Cast Iron
Impeller	Noryl / Cast Iron
Shaft	EN8 / SS410
Mechanical Seal	Carbon / Ceramic
Insulation	Class B / Class F
Motor Body	Aluminum / PDC



## SHALLOW WELL PUMPS

## PERFORMANCE TABLE

SR. No.	MODEL	H.P./KW	VOLTAGE (V)	SUPPLY TYPE	SUCTION X DELIVERY (mm)	HEAD IN METERS														
						4	8	12	16	20	24	28	30	32	32	34	36	40		
DISCHARGE IN LPH	0.5 SW+	0.5 / 0.37	220	1PH	25x25	3100	3000	2800	2400	2000	1500	900	550	200						
	0.5 SW	0.5 / 0.37	220	1PH	25x25	4050	3900	3870	3840	2600	2100	1440	780	400						
	1.0 SW+	1.0/0.75	220	1PH	25x25	3400	3200	3060	2800	2700	2300	1700	1400	1100	400					
	1.0 SW	1.0/0.75	220	1PH	25x25	3900	3840	3720	3600	3480	2820	2400	1600	1020	600					

NOTE: Technical details are approximate and may change due to site conditions or due to continuous improvement

CUSTOMER HELPLINE: 1800 4190 136