



Authorised dealer:



CIN-L34101KA1967PLC001706
Plot No.1 Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, India.



info@vsttractors.com

www.vsttractors.com

/vst-tillers

http://bit.ly/VSTVideos

company/vst-tillers

Grow with us

CUSTOMER HELPLINE: 1800 4190 136



DOMESTIC & AGRICULTURE PUMPS



PUMPS CATALOGUE & SELECTION GUIDE

Grow with us

CUSTOMER HELPLINE: 1800 4190 136

V FLOW PUMPS



FEATURES

Automatic coil winding and CNC technology

Thermal Overload Protector (TOP)

Double shielded pre-lubricated ball bearings

Less suction priming time

Suction lift up to 8mtr



APARTMENTS



GARDENING



VILLA

Grow with us



PRODUCT SPECIFICATIONS

Pump Sizes (MM): 25X25

Head (M): Up to 43

Discharge (LPH): Up to 3360

Power Range (HP): Up to 1.0

RPM: 2800 & 1440

Voltage Range (V): 160 to 240

MATERIAL OF CONSTRUCTION (MOC)

Pump Casing	Cast Iron
Impeller	Noryl / Cast Iron
Shaft	EN8 / SS410
Mechanical Seal	Carbon / Ceramic
Insulation	Class B / Class F
Motor Body	Aluminum / CI



V FLOW PUMPS

PERFORMANCE TABLE

SR. No.	MODEL	H.P./KW	VOLTAGE (V)	SUPPLY TYPE	RPM	SUCTION X DELIVERY (mm)	DISCHARGE IN LPH	HEAD IN METERS													
								3	6	9	12	15	18	21	24	27	30	33	36	43	
1	0.5 VF	0.5 / 0.37	220-240	1PH	2880	25x25	DISCHARGE IN LPH	2800	2700	2600	2400	2200	2060	1880	1650	1440	1200	970	650		
2	0.5 VF +	0.5/0.37	180-220	1PH	1440	25X25				2940	2520	2300	2020	1830	1520	1120	900	-	-		
3	1 VF	1.0/0.75	180-220	1PH	1440	25x25				3360	3240	3180	3060	2940	2700	2280	1800	1320	960	720	

NOTE: Technical details are approximate and may change due to site conditions or due to continuous improvement

CUSTOMER HELPLINE: 1800 4190 136