





VT VT-180D HS

- **Adjustable Rear Hitch For Varied Applications.**
- **Dry Type Air Cleaner For Improved Engine Performance.**
- **Best Suited Rotary For Both Wet And Dry Land Application.**
- **New Seat For Better Operator** Comfort.







SPECIFICATIONS

ENGINE

Engine Model K3C

3 Cylinder, 4 Stroke, Water Cooled, Type Indirect Injection, Naturally Aspirated,

Diesel Engine

900.51 cu.cm Displacement (CC)

Max. Torque 4.65 Kg-m (1900 rpm) 18.5 HP / 2700 rpm Output/Rated

Forced Circulation of Coolant & Water Cooling System

FUEL/AIR INTAKE SYSTEM

Fuel High Speed Diesel (H.S.D)

Fuel Tank Capacity 18 litres Air Cleaner Dry Type

ELECTRICAL SYSTEM

Starting System Starter Motor 12 Volts - 1.6 KW

Lighting 12 Volts, 35 Watts 12 Volts, 40 Amps Alternator

12 Volts Quick Heat Type Glow Plug

SALIENT FEATURES & BENEFITS

Improved Engine Performance Dry Type Air Cleaner

Adjustable Rear Hitch for Varied Adjustable Hitch

Applications

Best Suited Rotary for Both Wet & Rotary Sync

Dry Land Application

TRANSMISSION

Sliding Mesh Transmission 6 Speeds Forward 2 Speeds Reverse

Travelling Speed (kmph) 1.18 (min.) - 17.38 (max.) Power Take Off (P.T.O) 540 & 884@2340 RPM

Water Proof Internal Expanding Shoe Brake Type Brake with Parking Brake

Front 5-12, Rear 8-18 Track Width 810 & 885 Tyres

Width-1105mm; Height-1200mm; Overall Dimensions Length-2705mm; Wheel Base-1420mm

Ground Clearance 199 mm **Turning Radius** W/Brake 2.1 m

Haulage Capacity 2 Wheel Trailer, 3 Tonnes (Gross Weight)

Side Drive Type Rotary

Weight 840 Kgs (standard ballast wt)

HYDRAULIC SYSTEM

Hydraulic System Auto Draft & Depth Control

FIELD PERFORMANCE

Rotary 900 GTRI 1100 GTRI Tilling Width 900mm 1100mm No. of Tynes 20 Tilling Depth 150mm 150mm Plough Depth 220mm



Trust of >5 lakh farmers, Legacy of >50 years



Widest working range (3 HP to 50 HP)



No.1 Power Tiller brand for last 50 years



Pioneer in light weight **4WD compact Tractors**

Authorised Dealer



Global footprints in > 40 countries



Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA Phone: +91 - 80 - 67141111, e-mail: info@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice.





in /company/vst-tillers





June 2023