

# VST 130 DI POWER TILLER

A TRUST BUILT OVER DECADES



MADE IN INDIA



Powerful, 4 Stroke  
Water Cooled Engine



Robust  
Transmission



Light Weight



Easy Turning

1800 419 0136

exports@vst-international.com

www.vst-international.com

## COMPATIBLE ATTACHMENTS



Two Share Plough



Cultivator



Fertilizer Cum Seed Drill



Ridger (Furrower)



Reaper



Cage Wheel



HTP Sprayer



Potato Digger



Water Pump



Alternator



Trailer

and many more...

## TECHNICAL SPECIFICATIONS


<b>PRODUCT DETAILS</b>	Category	Power Tiller
	Model	VST SHAKTI 130 DI
	Type	General Purpose, Walk Behind Type
<b>ENGINE</b>	Type	Four Stroke, Single Cylinder, Horizontal, Over Head Valve, Compression Ignition, Diesel Engine
	Bore × Stroke, mm	95 × 95
	Displacement, cc	673.4
	Max. Power, HP @ RPM	13 @ 2400
	Starting System	Hand Cranking (Manual)
<b>TRANSMISSION</b>	Transmission Drive	Gear Drive
	Type	Combination Of Constant & Sliding Mesh
	Clutch	Dry, Multi Friction Plate
	No. of Speeds	08 (06- Forward & 02- Reverse)
	Transmission Oil Capacity, Ltr	6.0 (SAE 90)
	Brake System	Hand Operated Internal Expanding Metallic Shoe Type
	Wheels Type & Nos.	Pneumatic, Traction & 2 Nos.
<b>ROTARY</b>	Wheels Size	6.00 - 12, 4 PR
	No. of Tynes	18
	Rotary Speed	2
	Tilling width (max.), mm	600 (max.)
<b>PRODUCT OVERALL</b>	Tilling depth (max.), mm	Rotavation -140; Puddling - 200
	Overall Dimension (L × W × H), mm	2370 × 880 × 1260
	Gross Weight (with rotary), Kg	430

### APPLICATIONS:

Tillage Operation, Dry & Wet Land Operation, Earthing-up, Inter-cultivation, Land Preparation etc.

### SUITABLE FOR:

Sugarcane, Vegetables, Orchards, Horticulture, Plantation



Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA  
Phone: +91 - 80 - 67141111, e-mail: exports@vst-international.com, CIN: L34101KA1967PLC001706. [www.vst-international.com](http://www.vst-international.com)

Authorised Dealer

**Disclaimer:** Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.

1800 419 0136

/vsttillers

/company/vst-tillers

<http://bit.ly/VSTVideos>