

VST *Zetor*



TRUSTED. TIMELESS. **TOUGH**

**VST ZETOR
4211**

TECHNICAL SPECIFICATIONS

Model Name	VST ZETOR 4211	Model Name	VST ZETOR 4211
ENGINE		FUEL TANK	
Power at Rated RPM (HP)	42 @ 2100	Capacity (Litre)	60
No. of Cylinder	3	HYDRAULICS	
Displacement (CC)	2942	Three Point Linkage	CAT II
Air Cleaner	Dry Type	VZ Matic	yes
Torque Nm	180	Lifting Capacity (kg)	ADDC - 1800 KG
PTO		Spool Valve	DCV/QRC*
PTO HP	37	WHEEL	
PTO Type	540/ GSPTO	Wheel drive	2WD
TRANSMISSION		Front	6X16
Transmission Type	Helical Constant Mesh	Rear	13.6X28
No. of Gears	8+2	ELECTRICAL	
Shifting	Side Shift	Battery	12V, 88AH
Rear Axle Reduction	BullGear Pinion	Alternator	12V, 50A
Front Axle Reduction	Straight Axle	Starter Motor	12V, 2.7KW
SPEED & CLUTCH		DIMENSIONS	
Speed forward (kmph)	2.3 - 31.1	Overall Length (mm)	3570
Speed reverse (kmph)	2.9 - 11.6	Overall Width (mm)	1750
Forward Speed at flyup	33.9	Overall Height (mm)	2090
Clutch	Dual/Single*	Ground Clearance (mm)	420
BRAKES		Wheel Base (mm)	2100
Type	OIB	TCR with Brakes (mm)	3.1
SEAT		Total Weight (kgf) W/O ACCESSORIES	2080
Type	Premium VZ Seat		
		*Optional	

VST ZETOR PRIVATE LIMITED

Plot No-1, Dyavasandra Industrial Layout, Mahadevapura, Bengaluru - 560048, Karnataka, India.

e-mail: info@vstzetur.com; www.vstzetur.com

CIN: U28211KA2023PTC179152

1800 419 0136

SCAN TO FOLLOW US
ON SOCIAL MEDIA



Please contact your nearest dealership for latest updates

Authorised Dealer

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.