

VST Zetor



TRUSTED. TIMELESS. **TOUGH**

VST ZETOR
4511

TECHNICAL SPECIFICATIONS

Model Name	VST ZETOR 4511	Model Name	VST ZETOR 4511
ENGINE		FUEL TANK	
Power at Rated RPM (HP)	45 @ 2100	Capacity (Litre)	60
No. of Cylinder	3	HYDRAULICS	
Displacement (CC)	2942	Three Point Linkage	CAT II
Air Cleaner	Dry Type	VZ Matic	yes
Torque Nm	190	Lifting Capacity (kg)	ADDC - 1800 KG
PTO		Spool Valve	DCV
PTO HP	40.2	WHEEL	
PTO Type	540/ GSPTO	Wheel drive	2WD
TRANSMISSION		Front	6.5X16/6X16*
Transmission Type	Helical Constant Mesh	Rear	14.9X28/13.6X28*
No. of Gears	8+2	ELECTRICAL	
Shifting	Side Shift	Battery	12V, 88AH
Rear Axle Reduction	BullGear Pinion	Alternator	12V, 50A
Front Axle Reduction	Straight Axle	Starter Motor	12V, 2.7KW
SPEED & CLUTCH		DIMENSIONS	
Speed forward (kmph)	2.4 - 32.5	Overall Length (mm)	3570
Speed reverse (kmph)	3.1 - 12.1	Overall Width (mm)	1820
Forward Speed at flyup	35.5	Overall Height (mm)	2110
Clutch	Dual	Ground Clearance (mm)	440
BRAKES		Wheel Base (mm)	2100
Type	OIB	TCR with Brakes (mm)	3.1
SEAT		Total Weight (kgf) W/O ACCESSORIES	2140
Type	Premium VZ Seat		
		*Optional	

VST ZETOR PRIVATE LIMITED

Plot No-1, Dyavasandra Industrial Layout, Mahadevapura, Bengaluru - 560048, Karnataka, India.

e-mail: info@vstzetur.com; www.vstzetur.com

CIN: U28211KA2023PTC179152

1800 419 0136

SCAN TO FOLLOW US
ON SOCIAL MEDIA



Please contact your nearest dealership for latest updates

Authorised Dealer

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.