VST 932 DI

VST

MAKING FARMING A PLEASURE!

4WD 30 HP

- POWER
- SAVING
- COMFORT

JAPANESE TECHNOLOGY

DOUBLE ACTING POWER STEERING

SYNCHROMESH TRANSMISSION

SIDE SHIFT

OIL IMMERESED BRAKES

SMART HYDRAULICS

MOBILE CHARGER

exports@vst-international.com www.vst-international.com

VST 932 DI

SPECIFICATIONS

ENGINE

Power, HP	:	**30**
No. of Cylinders	:	3
Cubic Capcity, cc	:	1642
Engine RPM	:	2500
Cooling	:	Water Cooled
Torque Nm	:	109.4

POWER TAKE OFF

Power, HP	:	24 (17.89)
PTO Std.	:	Live PTO-540/540E, Mid PTO, RPTO

TRANSMISSION

Type	:	Fully Synchromesh
No. of Speeds	:	9F + 3R
Shifting	:	Side Shift
Differential Lock	:	Yes

SPEED & CLUTCH

Forward Speed, kmph	:	1.81 - 22.32
Reverse Speed, kmph	:	1.92 - 12.08
Clutch Type	:	Double

BRAKES

Brake Type	:	OIB

STEERING TYPE

Type	:	Double Acting Power Steering

HYDRAULICS

Type	:	ADDC
Lift Capacity	:	1250
3 Point Linkage	:	CAT-I

TYRE

Front	:	6x12 / 7x14*
Rear	:	9.5x20 / 11.2x24*

WEIGHTS & DIMENSIONS

Length, mm	:	2510
Width, mm	:	1130
Height, mm	:	1390
Wheelbase, mm	:	1520
Ground Clearance, mm	:	325
Weight, Kg	:	1240
Min Turning Radius, m	:	2.1

Trust of >5 Lakh Farmers, Legacy of >50 Years

Widest Product Range (2 HP to 50 HP)

No.1 Power Tiller Brand for Last 50 Years

Pioneer in 4WD Compact Tractors

Global Footprints in > 40 Countries

Year on Year Growth Rate > 20%

VST TILLERS TRACTORS LTD.

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048. Karnataka. INDIA
Phone: +91 - 80 - 67141111, e-mail: exports@vst-international.com
CIN: L34101KA1967PLC001706. **www.vst-international.com**

/vsttillers /company/vst-tillers

http://bit.ly/VSTVideos

Disclaimer : Pictures used here are for illustration purpose only. Product specification are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.