

WORLD-CLASS PERFORMANCE!



4WD **18 HP**



ROBUST 3-CYLINDER STAGE-V ENGINE



SMART HYDRAULICS WITH ADDC



DIRECT CONTROL VALVE



HYDRAULIC ASSISTED POWER STEERING



DRY AIR CLEANER



COMFORTABLE & ADJUSTABLE SEAT



SHORTER TURNING RADIUS



MOBILE CHARGER



SPECIFICATIONS

ENGINE

Power, HP	:	18
No. of Cylinders	:	3
Cubic Capacity, cc	:	900
Max. Torque	:	48.3
Engine RPM	:	2700
Air cleaner	:	Dry Type

POWER TAKE OFF

Power, HP	:	11.1
Pto Std.	:	540

TRANSMISSION

Type	:	Sliding Mesh Gear
No. of Speeds	:	6F+2R
Rear Axle Reduction Type	:	Bull Gear
Differential Lock	:	Yes

SPEED & CLUTCH

Forward Speed, kmph	:	1.53 - 17.3
Reverse Speed, kmph	:	1.95 - 8.58
Clutch Type	:	Single

BRAKES

Brake Type	:	Dry Disk Brake
------------	---	----------------

STEERING TYPE

Type	:	Manual/Hydraulic assisted power
------	---	---------------------------------

SEAT

Type	:	Adjustable driver seat
------	---	------------------------

HYDRAULICS

Type	:	ADDC
Lift Capacity	:	500 Kg
3 Point Linkage	:	CAT-I
Hydraulic Valve Type	:	1SA/1DA Direction Control Valve

WEIGHTS & DIMENSIONS

Length, mm	:	2930
Width, mm	:	1090
Height, mm	:	2050
Wheelbase, mm	:	1420
Ground Clearance, mm	:	255
Weight, Kg	:	880
Turning Radius, m	:	2.1

OTHER FEATURES

- Dowlraft Exhaust
- Battery Cut-off Switch
- ROPS (with Beacon lamp)
- Mobile Charger
- Rear-View Mirrors
- Direct Control Valve (DCV)

TYRE

TYRE	FRONT	REAR
Agri	5 x 12	8 X 18
Industrial	23 x 8.5 - 12	33 x 15.5 - 16.5
Turf	23 x 8.5 - 12	33 x 15.5 - 16.5



Trust of >5 Lakh Farmers,
Legacy of >50 Years



Widest Product Range
(2 HP to 50 HP)



No.1 Power Tiller Brand
for Last 50 Years



Pioneer in 4WD
Compact Tractors



Global Footprints
in > 40 Countries



Year on Year Growth
Rate > 20%

