

COMPACT FOR CREATING IMPACT



4WD **22 HP**

- ◆ **POWER**
- ◆ **SAVING**
- ◆ **COMFORT**



3-CYLINDER
STAGE-V ENGINE



DIRECT CONTROL
VALVE



SMART HYDRAULICS
WITH ADDC



SHORT TURNING
RADIUS



COMFORTABLE &
ADJUSTABLE SEAT



MOBILE
CHARGER



BONNET WITH
LOCK



SPECIFICATIONS

ENGINE

Power, HP	:	22
No. of Cylinders	:	3
Cubic Capacity, cc	:	980
Max. Torque	:	54
Engine RPM	:	3000
Air cleaner	:	Dry Type

POWER TAKE OFF

Power, HP	:	12.2
Pto Std.	:	540

TRANSMISSION

Type	:	Sliding Mesh Gear
No. of Speeds	:	6F+2R
Rear Axle Reduction Type	:	Bull Gear
Differential Lock	:	Yes

SPEED & CLUTCH

Forward Speed, kmph	:	1.69 - 19.22
Reverse Speed, kmph	:	2.17 - 9.53
Clutch Type	:	Single

BRAKES

Brake Type	:	Drum Type
------------	---	-----------

STEERING TYPE

Type	:	Manual/Power*
------	---	---------------

*Optional

SEAT

Type	:	Adjustable driver seat
------	---	------------------------

HYDRAULICS

Type	:	ADDC
Lift Capacity	:	500 Kg
3 Point Linkage	:	CAT-I
Hydraulic Valve Type	:	1SA/1DA Direction Control Valve

WEIGHTS & DIMENSIONS

Length, mm	:	2930
Width, mm	:	1130
Height, mm	:	2075
Wheelbase, mm	:	1420
Ground Clearance, mm	:	267
Weight, Kg	:	880
Turning Radius, m	:	2.7

OTHER FEATURES

- Downdraft Exhaust
- ROPS (With Beacon lamp)
- Rear view mirror
- Battery Cut-off Switch
- Mobile Charger

TYRE

TYRE	FRONT	REAR
Agri	5 x 12/6 x 12*	8 x 18/8.3x20*
Industrial	23 x 8.5 - 12	33 x 15.5 - 16.5
Turf	23 x 8.5 - 12	33 x 15.5 - 16.5



Trust of >5 Lakh Farmers,
Legacy of >50 Years



Widest Product Range
(2 HP to 50 HP)



No.1 Power Tiller Brand
for Last 50 Years



Pioneer in 4WD
Compact Tractors



Global Footprints
in > 40 Countries



Year on Year Growth
Rate > 20%

