

STABILATOR

THE MOST SUITABLE AND STABLE ROTARY TILLER



- 
Italian Technology
- 
Specially Designed Imported Blades
- 
Heavy Duty With Low Maintenance
- 
Fuel Savings



Applications

Primary and Secondary Tilling, Puddling, Seed Bed Preparation, Stubble Removing and Weeding



Crops

Paddy, Wheat, Maize, Sugarcane, Sorghum, Cotton, Tobacco, Banana, Orchards etc.



Soils

Customised Variants for all Types of Soils



Easy Finance

Customised Retail Schemes Available*



Service

Service and Spare Parts Available at Pan India Network



 1800 4190 136  www.vstractors.com

*Terms and conditions apply.

SPECIFICATIONS

Stabilator	Compact			Economy				Economy Plus			Paddy Plus		
	1200 CGL	1200 CGLS	1200 CGLM	1350 EGL	1600 EGL	1850 EGL	2100 EGL	1600 EGL+	1850 EGL+	2100 EGL+	1600 PGC+	1850 PGC+	2100 PGC+
Size (Feet)	4	4	4	4	5	6	7	5	6	7	5	6	7
Tractor Power (HP)	22-30	24-35	24-35	24-35	35-45	40-50	45-55	35-40	40-50	50-60	35-40	40-50	50-60
Working Width (mm)	1175	1229	1229	1335	1530	1780	2025	1470	1720	1965	1540	1770	1980
Tillage Depth (inch)	5	5	5 to 6	5 to 6	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 6	5 to 6	5 to 6
Rotor Speed (RPM)	215	218	180/260	218	218	218	218	180/260	180/260	180/260	180/247	180/247	180/247
Nos of Blade (L Type)	24	24	24	30	36	42	48	36	42	48	48	54	60
Gear Box Type	Single	Single	MS	Single	Single	Single	Single	Multi	Multi	Multi	Multi	Multi	Multi

Stabilator	Delux			Delux Plus			Supreme			Supreme Plus					
	1600 DGL	1850 DGL	2100 DGL	1600 DGL+	1850 DGL+	2100 DGL+	1600 SGL	1850 SGL	2100 SGL	1600 SGL+	1850 SGL+	2100 SGL+	2350 SGL+	2600 SGL+	2850 SGL+
Size (Feet)	5	6	7	5	6	7	5	6	7	5	6	7	8	9	10
Tractor Power (HP)	35-40	40-50	50-60	35-40	40-50	50-60	35-45	40-50	45-55	35-45	40-50	45-55	50-60	60-80	70-90
Working Width (mm)	1470	1720	1965	1470	1720	1965	1495	1735	2078	1490	1720	1980	2230	2480	2730
Tillage Depth (inch)	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7	5 to 7
Rotor Speed (RPM)	180/260	180/260	180/260	180/260	180/260	180/260	179/259	200/289	179/259	184/266	206/298	184/266	184/266	206/298	206/298
Nos of Blade (L/C Type)	36	42	48	36	42	48	36	42	48	36	42	48	54	60	66/72
Gear Box Type	Multi			Multi			Multi			Multi					

Manufactured by :



VST TILLERS TRACTORS LTD.

CIN-L34101KA1967PLC001706

Plot No.1 Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, India.



[f /vsttillers](#) [in /company/vst-tillers](#) [You Tube](#) <http://bit.ly/VSTVideos>

We reserve the rights to alter product specifications and design without prior notice.