

# VST 95 DI IGNITO POWER TILLER

SUPERIOR PRODUCT WITH SELF-START



MADE IN INDIA



Powerful 9 HP  
Diesel Engine



Self-Start Power Tiller  
in the Category



Powerful Transmission  
with PTO Option



Assurance of  
Service & Spare Parts

1800 419 0136

exports@vst-international.com

www.vst-international.com

## COMPATIBLE ATTACHMENTS




Plough



Cultivator



Ridger



Cage Wheel



Sprayer



Water Pump



Trailer

## TECHNICAL SPECIFICATIONS


|                        |                                   |   |
|------------------------|-----------------------------------|---|
| <b>PRODUCT DETAILS</b> | Category                          | Power Tiller  |
|                        | Model                             | VST 95 DI IGNITO  |
|                        | Type                              | General Purpose, Walk Behind Type   |
| <b>ENGINE</b>          | Type                              | Four Stroke, Single Cylinder, Vertical, Air Cooled, Compression Ignition, Diesel Engine |
|                        | Bore × Stroke, mm                 | 86 × 72   |
|                        | Displacement, cc                  | 418   |
|                        | Max. Power, HP @ RPM              | 9 @ 3600  |
|                        | Starting System                   | Recoil (Manual) & Self-Start (Battery)  |
| <b>TRANSMISSION</b>    | Transmission Drive                | Gear Drive  |
|                        | Type                              | Combination Of Constant & Sliding Mesh  |
|                        | Clutch                            | Dry, Multi Friction Plate   |
|                        | No. of Speeds                     | 08 (06- Forward & 02- Reverse)  |
|                        | Transmission Oil Capacity, Ltr    | 6.0 (SAE 90)  |
|                        | Brake System                      | Hand Operated Internal Expanding Metallic Shoe Type                                     |
|                        | Wheels Type & Nos.                | Pneumatic, Traction & 2 Nos.  |
| <b>ROTARY</b>          | Wheels Size                       | 6.00 - 12, 4 PR   |
|                        | No. of Tynes                      | 10  |
|                        | Rotary Speed                      | 2   |
|                        | Tilling Width (max.), mm          | 340 / 540 (Optional)  |
| <b>PRODUCT OVERALL</b> | Tilling Depth (max.), mm          | Rotavation - 140; Puddling - 200  |
|                        | Overall Dimension (L × W × H), mm | 2170 × 880 × 1290   |
|                        | Gross Weight (with rotary), Kg    | 330   |

### APPLICATIONS:

Tillage Operation, Dry & Wet Land Operation, Earthing-up, Inter-cultivation, Land Preparation etc.

### SUITABLE FOR:

Sugarcane, Vegetables, Orchards, Horticulture, Plantation



Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA  
Phone: +91 - 80 - 67141111, e-mail: exports@vst-international.com, CIN: L34101KA1967PLC001706. [www.vst-international.com](http://www.vst-international.com)

Authorised Dealer

**Disclaimer:** Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.

 1800 419 0136

 /vsttillers

 /company/vst-tillers

 <http://bit.ly/VSTVideos>